


KVM Switch

Slim-1U Series **USB+PS/2** **Dual Video** **OSD**



USB + PS/2 KVM Switch
with Dual Video
UDV-104D
UDV-108D

The **Slim NovaView KVM Switches, UDV-104D and UDV-108D** offer the most reliable and efficient way of managing multiple computers in server rooms where space is at a premium. On Screen Display (OSD) features computer naming, computer selection, status indication, auto scan and much more. Up to 64 servers can be easily managed by cascading multiple KVM switches to expand capacity. Revolutionized video enhancement technology ensures superb quality at resolutions up to 1920 x 1440. For secured connections and space saving, all **Slim NovaView KVM Switches** require just one HDB15 connector for each computer connection.

	Model	Video Channel No.	For computer with Interface	Suitable for	Cable
USB+PS/2 Universal	UDV-104D UDV-108D	2	PS/2 or USB	PS/2-server USB-Sun USB-Mac	CBMxxxH (PS/2) CBMxxxUH (USB) Second video cable required

With Dual Video

For **UDV-104D** and **UDV-108D**, the models are designed with Dual-Video. It's excellent for graphic designers, CAD/CAM designers to work efficiently.

Features

- › Cascade configuration expands system capability.
- › 1U-height form factor saves rack spaces.
- › Auto-scan function automatically selects computer sequentially.
- › Supports Microsoft IntelliMouse (Pro).
- › Assigns computers with individual names.
- › Identifies and selects computers by chosen names.
- › Programmable scan filters unused computers.
- › Stores system settings and name entries to non-volatile memory.
- › Password security locks computer from unauthorized access.
- › Complete control with easy-to-use OSD interface.
- › Hotkey functions allow easily computer access.
- › Keyboard states automatically saved and restored while switching computers.
- › Operating system independent and transparent to all applications.
- › Plug-n-play system configuration.
- › DDC2B compatible.
- › Optional module supports microphones and stereo speakers.
- › Supports SUN keyboard emulation.

Specifications

		UDV-104D	UDV-108D
Number of console ports		1	
Number of computer ports		4	8
On-screen display (OSD)		Yes	
Plug-n-play		Yes	
Hotkey control		Yes	
Computer name entry		14-character	
Security control		4-character password per computer	
Cable type		Max 30M (100ft) at Console Max 30M (100ft) at PC ports for PS/2 computer Max 5M at PC ports for USB computer	
Resolution		1920 x 1440, DDC2B	
Computer connectors	Keyboard + Mouse	HDB15 female (grey) x 4	HDB15 female (grey) x 8
	+ Monitor	with USB + PS/2 interface	
Console connectors	Second monitor	HDB15 male (blue) x 4	HDB15 male (blue) x 8
	Keyboard	PS/2 Mini-DIN 6 (female) x 1	
Console connectors	Mouse	PS/2 Mini-DIN 6 (female) x 1	
	Monitor	HDB15 female (blue) x 2	
Multimedia module (optional)		N / A	Yes

Connection Pattern

